

Product Data Sheets

PEARLESCENTS 2 MIL CAST

GENERAL DESCRIPTION:

The Pearlescents are polychromic, brightly colored, high gloss cast vinyl film series manufactured by a proprietary process. The films are opaqe, offer uniform printability, and can be used in a broad range of markets including automotive, marine, recreational vehicle and computerized signmaking.

PRODUCT DATA	VALUE		TEST METHOD
PHYSICAL PROPERTIES			
Outdoor Durability	Five (5) years (vertical exposure film)		
Thickness -mil (micron)	Adhesive:0.9-1.0(23-2Film:2.1(54)Liner:78# White Ble	+/- 10%	ASTM D 3652
Application Surface	Flat and simple curves		
Service Temp. Range	-50°F to 225°F (-46°C to 107°C)		
Min. Application Temp. ² 50°l	F (10°C)		
Shelf Life	Two (2) years stored at 73°F (23°C) and 50%+/- 5% R.H.		
Dimensional Stability (%)	-0.015 in. (0.4 mm)		On Al panel at 150°F (65°C) for 48 hr
Printability	Conventional and UV Curable - Flat and rotary screen printing		
Adhesion Value	Stainless Steel Substrate 180° Peel @ 10 in./Min. 73°F		ASTM 1000
Flammability	Self-extinguishing		
Chemical Resistance	Anti-freeze (24 hrs.) Detergent (24 hrs.) SAE 20 Motor Oil (24 hrs.) Gasoline (1 hr.) 10% HCL (10 min.) 10% NH4OH (10 min.)	No Effect No Effect No Effect No Effect No Effect No Effect	

1. May be reduced by extreme climate exposure. 2. Surface/Ambient Air. 3. Always pre-test inks and method. 4. 180° peel at 10 in/min based on three production run.; tested as per ASTM 1000.

Product Performance and Suitability All of the descriptive information and recommendations for the use of Smf products shall be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty. All purchases of Smf products shall be independently determine the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of Smf is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.